

HOUSEHOLD USES

●MARBLE AND ALABASTER

Clean with **Regular Kotton Klenser™**. On porous materials **Kotton Klenser™** may have a tendency to be absorbed. It is best to try a corner of material to see test results. On polished materials **Kotton Klenser™** will remove rust, stains, grease, etc. Sometimes you may want to use 4/0 steel wool for a light abrasive action. Polish with **Lemon-Oil Beeswax Polish** for a protective finish.

●HARD-SURFACED LEATHERS

Leather with a varnished finish or that has been tanned and sealed can be successfully cleaned with **Regular Kotton Klenser™**. Always test a small unnoticeable spot on your leather to see how it will clean as it is sometimes difficult to determine what sealer is on the leather.

●HIGH-GLOSS FINISHES

Oriental Lacquer Finishes, Mahogany, etc.

Regular Kotton Klenser™, if used very carefully, will remove dirt, wax, smoke stains and grease from these finishes. Always be careful to work a small area at a time so as not to dull the high-gloss or lacquer finish, and be sure to remove all cleaner from surface after use.

Lemon Oil Beeswax Polish will not restore nor maintain a high-gloss finish. It is suggested that only an oil polish be used to maintain a high-gloss finish.

GENERAL HOUSEHOLD USES

●UNFINISHED OR STRIPPED WOOD

Kotton Klenser™ Protective Wood Feeder can be used to give a natural wood finish to unfinished or freshly-stripped woods. When doing this, try an unnoticeable, small area to see if the results are what you desire. Keep in mind that some woods (especially some oaks) have acids which tend to not be compatible with **Protective Wood Feeder**. Follow the directions in Step 2 under Woods after making the determination to use **Protective Wood Feeder** for a natural wood finish.

●ALUMINUM WINDOW FRAMES, ETC.

Regular Kotton Klenser™ cleans without pitting.

●Antiquing Kit Finishes

Regular Kotton Klenser™ will not restore or repair an antiquing kit finish.

Keep **Regular Kotton Klenser™** on hand to clean tree sap from autos, hub caps, tar, whitewall tires, Formica, grease build-up on vent-a-hoods, walls, exhaust fans, and kitchen cabinets.

©Instructions/Products

REGULAR KOTTON KLENSER™

16oz Gallon

PROTECTIVE WOOD FEEDER

8oz 16oz Gallon

LEMON OIL BEESWAX POLISH

10oz Gallon

OIL PAINTING RESTORING OIL

6oz Gallon

KOTTON KLENSER™ 4/0 STEEL WOOL

6-Pad Package

©Graco Sales Co., Inc. d/b/a

KOTTON KLENSER™ PRODUCTS, INC.

P.O. BOX 1386 • 6400 Hwy 70 N.

Braden, TN 38010-1386

1-800-238-6969 • Fax 901-386-2773

www.KottonKlenser.com

email: kkclean@ix.netcom.com

ITEM	QUANTITY	SIZE	AMOUNT
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

TN Tax 9.25%

Discover

FedEx Ground Shipping



TOTAL \$ _____

Exp. Date _____

NAME _____

SHIPPING ADDRESS _____

CITY _____

STATE _____

ZIP _____

() _____

PHONE AC: _____

CLEAN IT!

From Kitchen Cabinets to Finest Antiques



REGULAR KOTTON KLENSER™
PROTECTIVE WOOD FEEDER
LEMON OIL BEESWAX POLISH
HEAVY DUTY (Metal) KOTTON KLENSER™
OIL PAINTING RESTORING OIL

©Graco Sales Co., Inc. d/b/a
KOTTON KLENSER™ PRODUCTS, INC.
 P.O. BOX 1386 • 6400 Hwy 70 N.
 Braden, TN 38010-1386
 1-800-238-6969 • Fax 901-386-2773
www.KottonKlenser.com

WOODS

CAUTION: To get the results you desire from each **Kotton Klenser™** product, always begin with an unnoticeable spot on the piece first. **Regular Kotton Klenser™** - like other products - can remove a finish if not handled with care. And be sure to remove cleaner completely after use. It is recommended that you use gloves when using **Kotton Klenser™** products.

REJUVENATING ORIGINAL OIL, WAX, or VARNISH FINISH on WOODS

STEP 1 Apply **Regular Kotton Klenser™** in manageable small area(s) of the piece with paint brush (in case of heavily dirt-coated or damaged finishes, apply with 4/0 steel wool). Leave on a few minutes or only long enough to clean; wipe off thoroughly. In cases of stubborn dirt, rub with 4/0 steel wool; repeat process if necessary.

STEP 2 Apply **Protective Wood Feeder** with brush. Let **Feeder** absorb into the wood (absorption time can vary from 6 to 12 hours). If wood absorbs the first coat immediately, reapply **Feeder**. After wood has absorbed the fine oils and conditioners, wipe excess **Feeder** off and buff following grain of wood with 4/0 steel wool.

STEP 3 Maintain the beautiful finish with regular applications of **Kotton Klenser™ Lemon Oil Beeswax Polish**.

FOR REJUVENATION of DAMAGED, ORIGINAL VARNISH FINISH on WOOD (Checking or Crocodile)

NOTE: Sometimes a finish in this condition is simply lying loosely on the wood. **Regular Kotton Klenser™** will lift loose finish and leave intact only the finish that is still adhering to the wood.

STEP 1 Apply **Regular Kotton Klenser™** liberally; let sit as long as 24 hours or until damaged finish is softened. Rub softened finish with 4/0 steel wool until heavy damage is rubbed off; finish rubbing until smooth with 4/0 steel wool. (Always follow the grain of the wood.)

STEP 2 Apply **Protective Wood Feeder**; let wood absorb until it can absorb no more. Wipe off excess with soft cloth, then buff off with 4/0 steel wool following grain of wood.

STEP 3 Apply **Kotton Klenser™ Lemon Oil Beeswax Polish** on a regular basis to keep wood in excellent condition.

CLEANING METAL(S)

Heavy Duty Kotton Klenser™ does not leave a residue or film on metals.

• BRIGHT METALS

Copper • Brass • Stainless • Chrome

STEP 1 Apply **Heavy Duty Kotton Klenser™** with paint brush or 4/0 steel wool. Allow liquefying; then wipe off thoroughly. On heavily soiled or tarnished metals, allow **Heavy Duty** to remain overnight. Re-apply **Heavy Duty**; let re-liquefy and use 4/0 steel wool where necessary; wipe off thoroughly. (**Heavy Duty** will not remove varnish or lacquer from metal.)

STEP 2 Retard your metals finger marking and readily re-tarnishing by regular use of **Kotton Klenser™ Lemon Oil Beeswax Polish**.

• PEWTER

Follow Step 1 for Bright Metals, but, as pewter is a soft metal, the 4/0 steel wool should be used very carefully so as not to scratch your metal. After cleaning, follow Step 2 for Bright Metals for a beautiful protective satin glow to your fine pewter.

• SILVER and SILVER-PLATE

Follow Step 1 for Bright Metals but eliminate using 4/0 steel wool if at all possible as silver and silver-plate will scratch. After cleaning, apply a coat of **Kotton Klenser™ Lemon Oil Beeswax Polish** to retard tarnishing and finger-marking.

PRODUCTS NEEDED for CLEANING METALS

Heavy Duty Kotton Klenser™...16oz.
.....gallon

Lemon Oil Beeswax Polish.....10oz.
.....gallon

4/0 Steel Wool.....6-pad pack



*Always wash any metal utensil or serving dish
with warm, mild soap and water
prior to food preparation.*

OIL PAINTINGS

DIRECTIONS for CLEANING OIL PAINTINGS

CAUTION: Always try an unnoticeable corner to be sure that the painting has a durable paint that can be cleaned and has not been damaged by oxidation, etc. **Regular Kotton Klenser™ is a wonderful material and has successfully cleaned hundreds of paintings, but Kotton Klenser™ as well as any other cleaner can remove the paint if not handled with the utmost care. Some paintings cannot be cleaned without removing some paint with the dirt. Do not over clean.**

STEP 1 Apply **Kotton Klenser™ Oil Painting Restoring Oil** with brush in a small space to be cleaned. Dab off with soft cloth or absorbent towel.

STEP 2 Then apply **Regular Kotton Klenser™** on the same small portion of painting. Use a medium bristle brush with bristles cut short in a stubble manner, always working in brush strokes in a good light. When you see dirt and film breaking, dab off thoroughly with soft absorbent cloth or towel. Never rub or scrub the surface of the painting, and always be sure to remove all cleaner.

STEP 3 Apply another coat of **Kotton Klenser™ Oil Painting Restoring Oil**. Dab off. Note how luster is restored and details are brought out.

Products Needed to Clean an Oil Painting

Regular Kotton Klenser™ 16oz.
.....gallon

Oil Painting Restoring Oil..6oz.
.....gallon

Soft Absorbent Towels or Cloth
Medium Soft Bristle Brush (cut bristles off about halfway)

OIL PAINTINGS

Gold and Gold Leaf

DIRECTIONS for CLEANING GOLD and GOLD LEAF

Apply **Regular Kotton Klenser™** gently in small area, being careful not to apply heavy pressure or scrub but to dab gently with very soft cloth or brush until dirt begins to loosen. Gently dab off residue, being sure to remove all cleaner from article being cleaned.